

| Contemporary

Luminaire Elysée 500/650.



In order to perpetuate the classic Elysée and meet current requirements, we have re-equipped this neoclassical lighting fixture with LED.

☑ The project meets the requirements of the Order of 27 December 2018 on the prevention, reduction and limitation of light pollution.



▼ MATERIALS AND FINISHES

- Class II luminaire
- Decorative dome
- Bell shape, spun aluminum.
- Only available in 34PDG suspended version.
- Other fixing options: catenary or Lyre for top fixing.
- 2 dimensions:
 - ELYSEE 500 Lower diameter 530mm, upper diameter 160mm, height 330mm
 - ELYSEE 650 Lower diameter 670mm, upper diameter 200mm, height 440mm
- Fixed on the board: one-piece Lolita body in die-cast aluminum casting Ø370mm
- Sealed, screen-printed LOLITA bowl
- in IK08 flat glass, as standard
- in IK10 polycarbonate, on request
- Aluminum strips between PCBs to reduce glare
- RAL / Akzo Nobel powder coating of your choice, seaside option on request

▼ EQUIPMENT

- OPTICAL BLOCK:
 - PMMA optical lenses
 - Aluminum PCB
 - Optics: Road (R), Semi-urban (SU), Urban (U), Square (P), Cycle path (PCY), Pedestrian crossing, Architectural.
 - Color temperatures: 3000K, 2700K, 2200K, 1800K (4000K, on request)
 - Coexistence of 2 optional color temperatures*.
 - Cable gland
 - Pre-wired HO7 RN-F flexible (Length depending on equipment)
 - ULR < 1%, ULR < 4% (in situ), CIE flux 3 code > 95%
- Integrated EQUIPMENT:
 - IP66 waterproofing
 - Driver Light prog, Driver Full prog (With DALI output on request). SR or D4I driver and socket, optional
 - *Additional driver for mixed temperature option
- ELECTRICAL PROTECTION:
 - 10kV surge protector on request
 - Varistor on request
- All our components are ENEC certified

▼ FIXINGS

- STANDARD :
- Suspended in 34 PdG

▼ DIMENSIONS

