

Luminaire Porthos.²



✔ The project meets the requirements of the Order of 27 December 2018 on the prevention, reduction and limitation of light pollution.



CHRYSA LIS



▼ MATERIALS AND FINISHES

- Luminaire comprising 3 extruded aluminum fixing arms
Compatible for top 60 pole
- Body of the luminaire in injected casting.
- IK08 screen-printed glass bowl
- RAL powder coating of your choice, seaside option on request.
Possibility of differentiating the color of the optical unit and the support.

▼ EQUIPMENT

- IP66 OPTICAL BLOCK:
 - Class II lighting
 - Equipment with 1 or 2 PCBs (16 LEDs or 32 LEDs, or equivalent)
 - PMMA lenses
 - Optics: Road (R), Semi urban (SU), Urban (U), Square (P), Cycle path (PCY), Pedestrian crossing.
 - Flow and output table identical to the Lolita luminaire, available on demand
 - Lifespan L90B10 100,000h
 - ULR < 1%, ULR < 4% (in situ), CIE flux 3 code > 95%
 - Color temperature: 3000K as standard. 2700, 2200 and 1800K in option.
 - Coexistence of 2 tones of white or a tone and a color for the preservation of particular fauna possible on request
- Standard length pre-wiring depending on the number of PCBs
- EQUIPMENT remote at the base of the pole:
 - IP66 waterproofing
 - Fullprog driver as standard with integrated 8KV mini protection. Liteprog and D4I driver optional.
- Compatible volumes for existing pole $\varnothing 90$ mm (to be communicated to the order). Specific driver(s) for mixed source solution on project
- OPTIONS:
 - Zhaga antenna socket on request
 - Varistor on request
 - All our components are ENEC certified

▼ FIXINGS

- STANDARD :
 - Covering end cap for 60mm top mast

▼ DIMENSIONS

